



# CLEAN-PRO

## TRT 9002

MAJ 24/12/09



# ANTI-SOIL TREATMENT

## CHARACTERISTICS

- Liquid
- Colourless
- Characteristic odour
- d = 0.8
- pH = 2
- Flash point: 15°C

## APPLICATIONS

- Maintenance
- Building industry
- Local & public authorities
- Automobile
- Transport

## BENEFITS

- Protective action with high persistence
- Reduced cleaning time
- Protection against atmospheric pollution

## LABELS



## PROPRIETIES

Invisible anti-soil protection.

Recommended for surfaces such as glass, polycarbonate, anodized aluminium, stainless steel, ceramics, enamels.

Powerful hydrophobic action.

Facilitates further routine cleaning.

Significant reduction of limestone and scale deposits.

Ideal for shower enclosures, windscreens, mirrors, glass surfaces, portholes, sinks, tiling, etc.

## INSTRUCTIONS FOR USE

Ready to use.

Apply to perfectly clean and dry surfaces.

Apply regularly to the whole surface in crossed passes using a dry and clean cloth.

Two layers are required.

Drying time: approx. two minutes.

Once the second layer is dry, wipe using a dry and clean cloth without exerting any pressure.

## PRECAUTIONS FOR USE

Easily flammable .

Do not apply to hot surfaces (evaporation too fast).

Do not apply to acrylic glass.

For further information, please refer to the safety datasheet.

## Chimie Recherche Environnement Evolution

ZAC des châtaigniers, 7 rue des entrepreneurs 95150 TAVERNY

Tél: 01.30.40.58.58 - Fax: 01.39.95.63.57

Site: <http://www.cree-sa.fr> - mail: [cree@cree-sa.fr](mailto:cree@cree-sa.fr)